

BULLETIN

PRODUCT SPECIFICATIONS

7023 Journeyman FLEX Steel

Journeyman FLEX Steel, Standard, Non-Belted

The Journeyman FLEX Steel continues the tradition of uncompromising performance you've come to rely on every day. New design elements have been incorporated into this jobsite workhorse for improved comfort, durability and reliability. The Journeyman FLEX Steel continues the tradition of keeping your team safe.

Features

- Durable alloy steel hardware
- Three D-rings; One Back and Two Hip
- Premium breathable padded air mesh shoulder yoke
- Quick Connect Visi-lock chest buckle
- 18" countoured leg pads
- Low-profile Torso Adjusters
- Tongue buckle Leg Adjusters
- Non-slip dorsal D-ring adjustment

MATERIALS SPECIFICATIONS

Webbing:	Polyester; Min. 5,000 lbs. tensile strength
Keepers:	Plastic
D-Rings:	Steel; Min. 5,000 lbs. tensile strength
Buckles/Adjusters:	Steel; Min. 3,375 lbs. tensile strength
Grommets:	Brass
Shoulder Adjusters:	Friction
Foam:	High density internal foam

PERFORMANCE SPECIFICATIONS

Maximum Working Load:	425 lbs.
ANSI User Capacity:	130 to 310 lbs. Max.
OSHA User Capacity:	130 to 425 lbs. Max.

SIZES

Style #	Description
PN 7023	UniFit
PN 7023XL	X Large
PN 70232X	2X Large
PN 70233X	3X Large
PN 70234X	4X Large
For shoulder and waist size ranges, please see Size Charts page.	



7023
Journeyman FLEX Steel

RELEVANT STANDARDS

ANSI:	Z359.11-2014
OSHA:	1926.502, 1910.66

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never attach a shock absorbing lanyard to a side D-Ring.