

CB SWIVEL TOP INSTRUCTIONS



General Description: The Guardian CB SWIVEL TOP is a roof mounted fall protection system designed for use on CB Series raised anchors. It allows workers free movement while tied off to an approved and already installed CB Series raised anchor.

WARNING:

The purchaser/user is solely responsible for attaching the Guardian CB SWIVEL TOP to a proper point in the roof. The attachment point must meet all Federal, State and Local regulations and OSHA (Fall Protection). The purchaser/user is also solely responsible for obtaining and using a harness and connecting equipment, as well as enforcing safe work practices when using this equipment.

1. Failure to install, use, and/or remove Guardian equipment in a safe and responsible manner can result in serious injury or death.
2. Read and understand all instructions, warnings, cautions, notes, etc. regarding the safe use of this safety equipment.
3. When installing, using and removing Guardian safety equipment, Federal, State and Local Laws and Regulations must be followed. Consult OSHA and ANSI for more information.
4. You must plan for and follow safe work practices for each installation and removal of this equipment.
5. If you have any questions regarding the safe installation, use, or removal of the equipment call Guardian at (800) 466-6385.

WARNING: Federal, State and Local standards and laws must be followed at all times. Failure to do so may result in serious injury or death.

INSTALLATION AND INSPECTION

1. Visually inspect the unit before installation:
 - a. CB Anchor
 - i. Assembly is free of damage including bends and welds.
 - b. CB SWIVEL TOP ANCHOR:
 - i. No physical damage to welds or pins.
2. **WARNING:** If the unit fails the visual inspection or test, do not use. Return to Guardian for repair. **DO NOT TRY TO REPAIR THE UNIT!**
3. Attach the unit to a proper anchorage point which is in line with and above the user (perpendicular to the edge). Never use an

anchorage point which is too far left or right of the user in order to minimize fall swing type injuries from the pendulum effect after a fall.

4. The CB SWIVEL TOP fastens to the top of the CB Raised Anchor (without attached horizontal lifeline) when the hole in the CB RAISED ANCHOR is aligned with the CB Raised Anchor's top attachment.

5. When the CB SWIVEL TOP's lower attachment hole is aligned with the CB Raised Anchor's top attachment, insert the locking hitch pin and secure the pin's locking pin.

6. Ensure that the CB SWIVEL TOP is properly installed by attempting to pull the CB SWIVEL TOP off of the CB Raised Anchor.

Installing the Retractable Lifeline

The Guardian CB SWIVEL TOP is designed to accept numerous manufacturers' retractable lifelines (fifty (50) foot in length maximum).

1. Remove clevis pin from retractable receiver wings.
2. Slide retractable horizontally into position.
3. Reinsert clevis pin and insert hitch pin.
4. Inspect and operate the retractable as per manufacturer's instructions.

WARNING: FAILURE TO FOLLOW THE RETRACTABLE MANUFACTURER'S INSTRUCTIONS COULD RESULT IN SEVERE INJURY OR DEATH.

MAINTENANCE

The following periodic routine maintenance actions are recommended:

- Perform the visual inspection and test described under INSTALLATION before use of each unit.

WARNING: WHENEVER UNIT HAS ARRESTED A FALL IT MUST BE RETURNED TO GUARDIAN FOR DISASSEMBLY, INSPECTION AND REPAIR OR REPLACEMENT FOR PARTS AS REQUIRED. DO NOT DISMANTLE UNIT.

If you have any further questions please contact Guardian Fall Protection, Kent WA at 800-466-6385.