

New! Miller® Arc-Rated Fall Protection Products

Meets Stringent
ASTM F887-05
Arc-Flash Standards!



New Miller® Arc-Rated Products are designed to protect workers from falls caused by electric arc-flash and arc-blast exposure when working at heights or in confined space applications near energized electrical sources.

All Miller® brand fall protection products meet applicable OSHA, ANSI and CSA requirements.



MILLER

by Honeywell

Miller® Arc-Rated Fall Protection Products



Model
RKNARRL-QC/UBK
shown



Miller Revolution™ Arc-Rated Harnesses

Featuring the same key elements that have made the Miller Revolution Harness the most comfortable and versatile harness available. Additional custom safety features have been incorporated for the security and protection of utility and maintenance workers.

- Kevlar®/Nomex® Miller DualTech™ webbing – patent-pending 10,000 lb. tensile strength webbing is engineered with permanent fire retardant (FR) properties. The webbing offers the durability and FR properties of Kevlar on the outer side, with softer FR Nomex on the inside of the webbing for greater comfort. The webbing assures arc protection and durability that eclipses any nylon webbing.
- PivotLink™ design allows unmatched freedom of motion and comfort, while the unique Cam Buckles provide easy two-finger adjustment
- Leather insulators under all metal hardware offer additional protection for the worker
- The Kevlar web loop on the back pad allows for a “metal-less” connection when used with a Kevlar shock-absorbing lanyard with a choke-off loop
- All Miller Revolution Arc-Rated Harnesses have bright red binding on every pad, making them easily identifiable as an arc-rated product

Miller Revolution Arc-Rated Harnesses with Kevlar/Nomex Webbing, Kevlar Web Loop and Leather Insulators under all hardware

Model	Size	Standard Features	Side D-Rings & Pad	Leg Strap Buckles	Rescue Loops	Special Features
RKNAR-QC/UBK	U	• Quick-Connect Chest Buckles	No	Quick-Connect	No	Leather insulators; web back D-ring
RKNAR-TB/UBK	U		No	Tongue	No	Leather insulators; web back D-ring
RKNAR-QC-BDP/UBK	U	• Cam Buckles	Yes	Quick-Connect	No	Leather insulators; web back D-ring; removable belt; side D-rings & pad
RKNAR-TB-BDP/UBK	U		Yes	Tongue	No	Leather insulators; web back D-ring; removable belt; side D-rings & pad
RKNARRL-QC/UBK	U	• ErgoArmor Back Shield	No	Quick-Connect	Yes	Leather insulators; web back D-ring
RKNARRL-TB/UBK	U		No	Tongue	Yes	Leather insulators; web back D-ring
RKNARRL-QC-BDP/UBK	U	• Self-Contained Label Pack	Yes	Quick-Connect	Yes	Leather insulators; web back D-ring; removable belt; side D-rings & pad
RKNARRL-TB-BDP/UBK	U		Yes	Tongue	Yes	Leather insulators; web back D-ring; removable belt; side D-rings & pad

Miller Heavy-Duty Arc-Rated Harnesses with Kevlar Webbing

Model	Size	Back D-Ring	Front D-Ring	Side D-Rings	Shoulder Strap Buckles	Leg Strap Buckles	Chest Strap Buckle	Sub-Pelvic Strap	Special Features
850KQC/UBK	U	Yes	Option	No	Friction	Quick-Connect	Quick-Connect	Yes	Leather insulators; pull-down adjustment; web back D-ring
650KQC-4/UBK	U	Yes	Option	No	Friction	Tongue	Quick-Connect	Yes	Leather insulators; pull-up adjustment; web back D-ring
650KQC-58/UBK	U	Yes	Option	Yes	Friction	Tongue	Quick-Connect	Yes	Leather insulators; pull-up adjustment; web back D-ring; side D-rings for positioning
850KQC-4/UBK	U	Yes	Option	No	Friction	Tongue	Quick-Connect	Yes	Leather insulators; pull-down adjustment; web back D-ring
850KQC-58/UBK	U	Yes	Option	Yes	Friction	Tongue	Quick-Connect	Yes	Leather insulators; pull-down adjustment; web back D-ring; side D-rings for positioning



850KQC-58/UBK

Model	Description
8928K/18INBK	Harness Back D-Ring Extension, Kevlar Webbing, 18 Inches

Miller® Arc-Rated Lanyards

Available in stretchable tubular or SofStop® pack styles, these shock-absorbing lanyards feature arc-rated Kevlar® webbing in both single- and double-legged models. Available with choke-off loop or locking snap hooks with 3/4-inch or 2-1/2 inch gate openings.



233MK/6FTBK



8799K/6FTBK

Model	Material	Style	Number of Legs	Harness Connection	Anchorage Connection	Standard Length*
216MK/6FTBK	Kevlar Webbing	Manyard II Lanyard	One	Locking snap hook	Locking snap hook	6' (1.8m)
219MK/6FTBK	Kevlar Webbing	Manyard II Lanyard	One	Locking snap hook	Locking rebar hook	6' (1.8m)
231MK/6FTBK	Kevlar Webbing	Manyard II Lanyard	Two	Locking snap hook	Locking rebar hooks	6' (1.8m)
232MK/6FTBK	Kevlar Webbing	Manyard II Lanyard	Two	Locking snap hook	Locking snap hooks	6' (1.8m)
233MK/6FTBK	Kevlar Webbing	Manyard II Lanyard	One	Choke-off loop	Locking snap hook	6' (1.8m)
233MRK/6FTBK	Kevlar Webbing	Manyard II Lanyard	One	Choke-off loop	Locking rebar hook	6' (1.8m)
266MK/6FTBK	Kevlar Webbing	Manyard II Lanyard	Two	Choke-off loop	Locking snap hooks	6' (1.8m)
266MRK/6FTBK	Kevlar Webbing	Manyard II Lanyard	Two	Choke-off loop	Locking rebar hooks	6' (1.8m)
913K/6FTBK	Kevlar Webbing	Lanyard w/SofStop Shock Absorber	One	Locking snap hook	Locking snap hook	6' (1.8m)
913KR/6FTBK	Kevlar Webbing	Lanyard w/SofStop Shock Absorber	One	Locking snap hook	Locking rebar hook	6' (1.8m)
933K/6FTBK	Kevlar Webbing	Lanyard w/SofStop Shock Absorber	One	Choke-off loop	Locking snap hook	6' (1.8m)
933KR/6FTBK	Kevlar Webbing	Lanyard w/SofStop Shock Absorber	One	Choke-off loop	Locking rebar hook	6' (1.8m)
8798K/6FTBK	Kevlar Webbing	Lanyard w/SofStop Shock Absorber	Two	Locking snap hook	Locking snap hooks	6' (1.8m)
8798KR/6FTBK	Kevlar Webbing	Lanyard w/SofStop Shock Absorber	Two	Locking snap hook	Locking rebar hooks	6' (1.8m)
8799K/6FTBK	Kevlar Webbing	Lanyard w/SofStop Shock Absorber	Two	Choke-off loop	Locking snap hooks	6' (1.8m)
8799KR/6FTBK	Kevlar Webbing	Lanyard w/SofStop Shock Absorber	Two	Choke-off loop	Locking rebar hooks	6' (1.8m)
928KLS/18INBK	Kevlar Webbing	SofStop Shock Absorber Pack Extension	One	Locking snap hook	D-Ring	18' (457mm)
940K/6FTBK**	Kevlar Webbing	Lanyard w/SofStop Double Pack	One	Locking snap hook	Locking snap hook	6' (1.8m)
940KR/6FTBK**	Kevlar Webbing	Lanyard w/SofStop Double Pack	One	Locking snap hook	Locking rebar hook	6' (1.8m)
943K/6FTBK**	Kevlar Webbing	Lanyard w/SofStop Double Pack	One	Choke-off loop	Locking snap hook	6' (1.8m)
943KR/6FTBK**	Kevlar Webbing	Lanyard w/SofStop Double Pack	One	Choke-off loop	Locking rebar hook	6' (1.8m)

*Available in lengths from 4 ft. (1.2m) to 10 ft. (3m).

**Double SofStop pack for 12 ft. (3.7m) free-fall/duty-rated 400 lbs. (181.4kg) capacity.

Note: Locking Snap Hook – 3/4-inch (19mm) gate opening; Locking Rebar Hook – 2-1/2 inch (63mm) gate opening.

Miller® Arc-Rated Fall Protection Products

Miller Arc-Rated Cross-Arm Anchorage Straps

Features Kevlar® webbing with 2-in. D-ring and choke-off loop.

Model	Material	Style	Length
8185K/3FTBK	Kevlar Webbing	Cross-Arm Strap	3' (1.0m)
8185K/6FTBK	Kevlar Webbing	Cross-Arm Strap	6' (1.8m)
8185K/10FTBK	Kevlar Webbing	Cross-Arm Strap	10' (3.0m)

*Available in lengths from 2 ft. (.6m) to 10 ft. (3m).



Leather Utility Bag

Specialty tool bag features multiple compartments and durable, oil-tanned leather construction. Designed to attach directly to the Revolution harness by simply snapping on or off.

Model	Material	Description
RIA-T11/1	Leather	Utility Bag



This equipment should only be used after reading the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.



by Honeywell

 Ask the Expert ... Ask Miller.

800/873-5242
or 814/432-2118

Fax 800/892-4078
or Fax 814/432-2415

www.millerfallprotection.com

For more information or to place an order,
please contact your Miller® distributor:

LMAR/0307/20M/RPI